


REV.	DESCRIPTION	DATE	BY



STYLE A - STEEL PLATE BONDED BETWEEN NR AND FLATBACK PADS

PER CUSTOMER SPECIFICATION




STYLE B - NR WITH LOAD PLATE AND HOLE

PER CUSTOMER SPECIFICATION



STYLE C -NR WITH LOAD PLATE AND COUNTER-BORED HOLE

PER CUSTOMER SPECIFICATION



STYLE D -NR WITH LOAD PLATE AND TAPPED HOLE



STYLE E -GALVANIZED STEEL PLATE BONDED BETWEEN MULTIPLE NR PADS

SIZE	LENGTH (IN.)	WIDTH (IN.)	HEIGHT FOR STYLE (IN.)				LOAD RANGE E*	
			A	B	C	D		
22	2	2	7/8	5/8	3/4	3/4	13/16	20-200
33	3	3	7/8	5/8	3/4	3/4	13/16	45-450
44	4	4	7/8	5/8	3/4	3/4	13/16	80-800
55	5	5	7/8	5/8	7/8	7/8	13/16	125-1250
66	6	6	7/8	5/8	7/8	7/8	13/16	180-1800
88	8	8	1	3/4	1	1	13/16	320-3200
99	9	9	1	3/4	1	1	13/16	405-4050

* THIS HEIGHT BASED ON TWO NR PADS. FOR EACH ADDITIONAL NR PAD COMBINED, ADD 7/16"

NOTES:

- 1) FINISH INDUSTRIAL GRADE ENAMEL.
- 2) CUSTOM SIZES AVAILABLE UPON REQUEST

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.



DFA Sales
www.Korfund.com
info@Korfund.com

MODEL SP-NR 20-4050 LBS.
 ELASTOMERIC ISOLATION PAD BONDED TO STEEL PLATE STYLE A THRU E

SCALE :

NONE

SHEET:



DRAWING NO.:

REVISION